

## Linatex in a Linagard ozone-resistant version

ISO	NR Natural Rubber
Shape	Rolls
Color	Black
Temperature Range	-40 and 70 °C
Density	980 kg/m <sup>3</sup>
Hardness	40 Shore A
Elongation at break	750 %
Tensile strength	21 N/mm <sup>2</sup>

### Material information

Measurement tolerance 7715-P3

This material has the distinctive qualities of Linatex, extremely hard-wearing and durable. This special is great for use where there is exposure to UV and/or OZON.

Petrol	Oil	UV	Water	Wear resistance	Acids	Alkali	Base
Not suitable	Not suitable	Excellent	Not suitable	Excellent	Low	Not suitable	Not suitable

### Item Overview

Item Code	Item Name	Width (mm)	Length (mm)
13000030	NR Linagard OZ zwart 3 mm	1.230	9.250
13000050	NR Linagard OZ zwart 5 mm	1.230	9.250

### Storage advice (ISO 2230)

The enclosed specification gives an indication of the storage periods to prevent degradation in properties of the material. Exposure to light and moisture should be avoided as much as possible. It is advisable to check the material in advance if it is to be stored for more than one year.

Group	Minimum temperature	Maximum temperature	Maximum humidity	Shelf life	Extension after inspection
A	10 °C	25 °C	65 %	5 year	2 year

We provide product information as known by us with great care. We cannot accept any liability for errors and/or inaccuracies and/or incompleteness. Please note that our products are intended for professional use only. For high impact applications and/or combinations of limit values we always recommend to have the properties specific to that situation verified by us. If there are multiple specifications for a product we will use the standard of 2mm or the closest specification.

