

Linard HDS is a Linatex suitable for high impact applications

Shape	Rolls
Color	Red
Temperature Range	-40 and 75 °C
Density	980 kg/m3
Hardness	70 Shore A
Elongation at break	580 %
Tensile strength	21,400 N/mm2

## Material information

Linatex HDS is a linatex special that is harder than standard linatex. The material is even more rigid because of this, this material lends itself extremely well to the mining industry.

## Usage examples

Recommended for applications where wear from highly abrasive dry media occurs.

Measurement tolerance 7715-P3

Petrol	Oil	UV	Water	Wear resistance	Acids	Alkali	Base
Not suitable	Not suitable	Not suitable	Excellent	Excellent	Not suitable	Not suitable	Not suitable

## Item Overview

Item Code	Item Name	Width (mm)	Length (mm)
13100080	NR Linard HDS 70 Shore rood 8 mm	1.230	9.250
13100100	NR Linard HDS 70 Shore rood 10 mm	1.230	9.250

*We provide product information as known by us with great care. We cannot accept any liability for errors and/or inaccuracies and/or incompleteness. Please note that our products are intended for professional use only. For high impact applications and/or combinations of limit values we always recommend to have the properties specific to that situation verified by us. If there are multiple specifications for a product we will use the standard of 2mm or the closest specification.*

