

EPDM sponge rubber tape suitable as hatch gasket in shipping industry

ISO	EPDM Terpolymre of ethylene, propylene and a diene (unsaturated diene in side chain)
Shape	shape_70
Color	Black
Temperature Range	-30 and 110 °C
Density	450 kg/m3
Hardness	15 Shore A (± 5)

Material information

Soft quality EPDM sponge rubber with extrusion skin suitable as hatch gasket. Closed cell structure with less than 10% open cells. Highly weather resistant and seawater resistant.

Usage examples

Hatch gasket on (sea) ships, or as a seal on other doors. Due to the soft quality suitable for lighter hatches

Processing

Supplied on tape and easy to cut or trim to size.
Measurement tolerance 7715-P3

Petrol	Oil	UV	Water	Acids	Alkali
Not suitable	Not suitable	Excellent	Excellent	Low	Low

Item Overview

Item Code	Item Name	Width (mm)	Length (mm)
38000808	EPDM Sponsrubber 15 Shore 8x8 mm		100.000
38001005	EPDM Sponsrubber 15 Shore 10x5 mm		50.000
38001006	EPDM Sponsrubber 15 Shore 10x6 mm		100.000
38001010	EPDM Sponsrubber 15 Shore 10x10 mm		50.000
38001204	EPDM Sponsrubber 15 Shore 12x4 mm		100.000
38001208	EPDM Sponsrubber 15 Shore 12x8 mm		50.000
38001212	EPDM Sponsrubber 15 Shore 12x12 mm		50.000
38001504	EPDM Sponsrubber 15 Shore 15x4 mm		50.000
38001505	EPDM Sponsrubber 15 Shore 15x5 mm		100.000
38001510	EPDM Sponsrubber 15 Shore 15x10 mm		50.000
38001515	EPDM Sponsrubber 15 Shore 15x15 mm		50.000
38002005	EPDM Sponsrubber 15 Shore 20x5 mm		50.000
38002010	EPDM Sponsrubber 15 Shore 20x10 mm		25.000
38002015	EPDM Sponsrubber 15 Shore 20x15 mm		25.000
38002020	EPDM Sponsrubber 15 Shore 20x20 mm		25.000
38002505	EPDM Sponsrubber 15 Shore 25x5 mm		100.000



38002508	EPDM Sponsrubber 15 Shore 25x8 mm	50.000
38002510	EPDM Sponsrubber 15 Shore 25x10 mm	25.000
38002512	EPDM Sponsrubber 15 Shore 25x12 mm	50.000
38002515	EPDM Sponsrubber 15 Shore 25x15 mm	25.000
38002520	EPDM Sponsrubber 15 Shore 25x20 mm	25.000
38002525	EPDM Sponsrubber 15 Shore 25x25 mm	25.000
38002828	EPDM Sponsrubber 15 Shore 28x28 mm	25.000
38003003	EPDM Sponsrubber 15 Shore 30x3 mm	50.000
38003004	EPDM Sponsrubber 15 Shore 30x4 mm	50.000
38003005	EPDM Sponsrubber 15 Shore 30x5 mm	50.000
38003010	EPDM Sponsrubber 15 Shore 30x10 mm	25.000
38003015	EPDM Sponsrubber 15 Shore 30x15 mm	25.000
38003020	EPDM Sponsrubber 15 Shore 30x20 mm	25.000
38003025	EPDM Sponsrubber 15 Shore 30x25 mm	25.000
38003030	EPDM Sponsrubber 15 Shore 30x30 mm	25.000
38003510	EPDM Sponsrubber 15 Shore 35x10mm	25.000
38003520	EPDM Sponsrubber 15 Shore 35x20 mm	25.000
38003525	EPDM Sponsrubber 15 Shore 35x25 mm	25.000
38003530	EPDM Sponsrubber 15 Shore 35x30 mm	15.000
38003535	EPDM Sponsrubber 15 Shore 35x35 mm	15.000
38004003	EPDM Sponsrubber 15 Shore 40x3 mm	50.000
38004005	EPDM Sponsrubber 15 Shore 40x5 mm	50.000
38004010	EPDM Sponsrubber 15 Shore 40x10 mm	25.000
38004015	EPDM Sponsrubber 15 Shore 40x15 mm	25.000
38004020	EPDM Sponsrubber 15 Shore 40x20 mm	25.000
38004025	EPDM Sponsrubber 15 Shore 40x25 mm	25.000
38004030	EPDM Sponsrubber 15 Shore 40x30 mm	15.000
38004035	EPDM Sponsrubber 15 Shore 40x35 mm	15.000
38004040	EPDM Sponsrubber 15 Shore 40x40 mm	10.000
38004520	EPDM Sponsrubber 15 Shore 45x20 mm	25.000
38004530	EPDM Sponsrubber 15 Shore 45x30 mm	15.000
38005004	EPDM Sponsrubber 15 Shore 50x4 mm	50.000
38005005	EPDM Sponsrubber 15 Shore 50x5 mm	50.000
38005010	EPDM Sponsrubber 15 Shore 50x10 mm	25.000



38005015	EPDM Sponsrubber 15 Shore 50x15 mm	25.000
38005020	EPDM Sponsrubber 15 Shore 50x20 mm	25.000
38005025	EPDM Sponsrubber 15 Shore 50x25 mm	15.000
38005030	EPDM Sponsrubber 15 Shore 50x30 mm	15.000
38005050	EPDM Sponsrubber 15 Shore 50x50 mm	10.000
38006015	EPDM Sponsrubber 15 Shore 60x15 mm	15.000
38007040	EPDM Sponsrubber 15 Shore 70x40 mm	10.000
38008040	EPDM Sponsrubber 15 Shore 80x40 mm	20.000

Storage advice (ISO 2230)

The enclosed specification gives an indication of the storage periods to prevent degradation in properties of the material. Exposure to light and moisture should be avoided as much as possible. It is advisable to check the material in advance if it is to be stored for more than one year.

Group	Minimum temperature	Maximum temperature	Maximum humidity	Shelf life	Extension after inspection
C	10 °C	25 °C	65 %	10 year	5 year

We provide product information as known by us with great care. We cannot accept any liability for errors and/or inaccuracies and/or incompleteness. Please note that our products are intended for professional use only. For high impact applications and/or combinations of limit values we always recommend to have the properties specific to that situation verified by us. If there are multiple specifications for a product we will use the standard of 2mm or the closest specification.

