

EPDM sponge rubber tape suitable as hatch gasket in shipping industry

ISO	EPDM Terpolymre of ethylene, propylene and a diene (unsaturated diene in side chain)
Shape	shape_70
Color	Black
Temperature Range	-30 and 110 °C
Density	450 kg/m ³
Hardness	25 Shore A (± 5)

Material information

Soft quality EPDM sponge rubber with extrusion skin suitable as a hatch gasket. Closed cell structure with less than 10% open cells. Highly weather resistant and seawater resistant. Tested for ozone resistance for 70 hours at 20% with no cracks in the material.

Usage examples

Hatch gasket on (sea) ships, or as a seal on other doors. Due to the hard quality suitable for heavier hatches.

Processing

Supplied on tape and easy to cut or trim to size.
Measurement tolerance 7715-P3

Petrol	Oil	UV	Water	Acids	Alkali
Not suitable	Not suitable	Excellent	Excellent	Low	Low

Item Overview

Item Code	Item Name	Width (mm)	Length (mm)
38201010	EPDM Sponsrubber 25 Shore 10x10 mm (laatste voorraad niet meer leverbaar)		50.000
38201212	EPDM Sponsrubber 25 Shore 12x12 mm		50.000
38202515	EPDM Sponsrubber 25 Shore 25x15 mm (laatste voorraad niet meer leverbaar)		25.000
38202520	EPDM Sponsrubber 25 Shore 25x20 mm (laatste voorraad niet meer leverbaar)		25.000
38202525	EPDM Sponsrubber 25 Shore 25x25 mm (laatste voorraad niet meer leverbaar)		25.000
38203015	EPDM Sponsrubber 25 Shore 30x15 mm (laatste voorraad niet meer leverbaar)		25.000
38203020	EPDM Sponsrubber 25 Shore 30x20 mm		25.000
38203030	EPDM Sponsrubber 25 Shore 30x30 mm		25.000
38203510	EPDM Sponsrubber 25 Shore 35x10 mm (laatste voorraad niet meer leverbaar)		25.000
38203520	EPDM Sponsrubber 25 Shore 35x20 mm		25.000
38204010	EPDM Sponsrubber 25 Shore 40x10 mm		25.000
38204020	EPDM Sponsrubber 25 Shore 40x20 mm		25.000
38204030	EPDM Sponsrubber 25 Shore 40x30 mm		25.000



38205015	EPDM Sponsrubber 25 Shore 50x15 mm (laatste voorraad niet meer leverbaar)	25.000
38205020	EPDM Sponsrubber 25 Shore 50x20 mm (laatste voorraad niet meer leverbaar)	25.000
38205025	EPDM Sponsrubber 25 Shore 50x25 mm (laatste voorraad niet meer leverbaar)	25.000
38205040	EPDM Sponsrubber 25 Shore 50x40 mm	10.000
38206020	EPDM Sponsrubber 25 Shore 60x20 mm (laatste voorraad niet meer leverbaar)	25.000
38206040	EPDM Sponsrubber 25 Shore 60x40 mm	10.000

Storage advice (ISO 2230)

The enclosed specification gives an indication of the storage periods to prevent degradation in properties of the material. Exposure to light and moisture should be avoided as much as possible. It is advisable to check the material in advance if it is to be stored for more than one year.

Group	Minimum temperature	Maximum temperature	Maximum humidity	Shelf life	Extension after inspection
C	10 °C	25 °C	65 %	10 year	5 year

We provide product information as known by us with great care. We cannot accept any liability for errors and/or inaccuracies and/or incompleteness. Please note that our products are intended for professional use only. For high impact applications and/or combinations of limit values we always recommend to have the properties specific to that situation verified by us. If there are multiple specifications for a product we will use the standard of 2mm or the closest specification.

