

Food-safe pure PTFE fiber cord gasket without lubricant

Shape [shape_70](#)
Color White
Temperature Range -268 and 280 °C
Maximum pressure 250 bar

Material information

Solid woven gasket made of pure ePTFE filaments. The material is pretreated but contains no lubricants. Resistant to aggressive substances, gases and solvents. Suitable for shaft speed of 5 m/s and has a wide pH range between 0 and 14.

Usage examples

Commonly used in sealing valves and other slow-moving applications.

Processing

To be cut to length from the roll
Measurement tolerance 7715-P3

Item Overview

Item Code	Item Name	Width (mm)	Length (mm)
58600505	Teadit 2005 Food Contact (2kg/doos=ca.50m) Afm. 5x5mm		
58600606	Teadit 2005 Food Contact (2kg/doos=ca.30m) Afm. 6x6mm		
58600808	Teadit 2005 Food Contact (2kg/doos=ca.19,6m) Afm. 8x8mm		
58601010	Teadit 2005 Food Contact (2kg/doos=ca.12,5m) Afm: 10x10mm		
58601212	Teadit 2005 Food Contact (3kg/doos=ca.13m) Afm 12x12mm		
58601414	Teadit 2005 Food Contact (3kg/doos=ca.9,6m) Afm 14x14mm		
58601616	Teadit 2005 Food Contact (5kg/doos=ca.12,3m) Afm 16x16mm		
58602020	Teadit 2005 Food Contact (5kg/doos=ca.8m) Afm 20x20mm		
58602525	Teadit 2005 Food Contact (?kg/doos=ca.?m) Afm 25x25mm		

We provide product information as known by us with great care. We cannot accept any liability for errors and/or inaccuracies and/or incompleteness. Please note that our products are intended for professional use only. For high impact applications and/or combinations of limit values we always recommend to have the properties specific to that situation verified by us. If there are multiple specifications for a product we will use the standard of 2mm or the closest specification.

